

Armoured Cable Glands



Order Encoding						
Part Number	Size	•M: Metric •N: NPT Thread	•C: Chloroprene Sealing	•B: Brass •X: Stainless steel •BN: Nickel Plated •A: Aluminium Material	Locknut	•S: Shroud
KBET	5	M	C	B	L	S

Thread Type METRIC acc. to EN 60423

Size	Clamping Range	Armour Wire	Thread Length	Thread Ø	SW Cap	Spanner Width SW Middle Body	SW Lower Body	Outer Ø	max. Height	Part Number	Packing Unit
	Ø min-max mm	Ø min-max mm	TL mm	TD mm							
M16x1,5	8,0 - 15,0	0,3 - 1,3	9,0	16,0	25	25	24	27,5	40,5	KBET01MC	100
M20x1,5	8,0 - 15,0	0,3 - 1,3	9,0	20,0	25	25	24	27,5	40,5	KBET1MC	50
	13,5 - 21,0	0,4 - 1,3			30	30	29	33,0	41,5	KBET1LMC	
M25x1,5	8,0 - 15,0	0,3 - 1,3	9,0	25,0	25	25	25	27,5	40,5	KBET2SMC	50
	13,5 - 21,0	0,4 - 1,3			30	30	29	33,0	41,5	KBET2MC	
	18,0 - 27,0	0,4 - 1,6			40	40	40	44,5	48,2	KBET2LMC	
M32x1,5	18,0 - 27,0	0,4 - 1,6	9,0	32,0	40	40	40	44,5	48,2	KBET3SMC	30
	23,0 - 33,0	0,4 - 2,0			43	43	43	48,5	51,7	KBET3MC	
M40x1,5	29,0 - 40,0	0,4 - 2,0	9,0	40,0	52	52	52	59,0	55,2	KBET4MC	25
M50x1,5	35,0 - 48,0	0,4 - 2,5	9,0	50,0	60	60	60	66,5	67,5	KBET5SMC	20
	42,0 - 56,0	0,6 - 2,5			75	74	70	83,0	74,3	KBET5MC	
M63x1,5	42,0 - 56,0	0,6 - 2,5	9,0	63,0	75	74	70	83,0	74,3	KBET6SMC	10
	53,0 - 66,0				85	85	80	94,0	75,3	KBET6MC	
M75x1,5	53,0 - 66,0	0,6 - 2,5	9,0	75,0	85	85	80	94,0	75,3	KBET7SMC	5
	63,0 - 75,0				95	95	90	105,0	78,8	KBET7MC	

Thread Type NPT acc. to ANSI B1.20.1

Size	Clamping Range	Armour Wire	Thread Length	Thread Ø	SW Cap	Spanner Width SW Middle Body	SW Lower Body	Outer Ø	max. Height	Part Number	Packing Unit
	Ø min-max mm	Ø min-max mm	TL mm	TD mm							
NPT 3/8"	8,0 - 15,0	0,3 - 1,3	16,0	17,1	25	25	24	27,5	40,5	KBET01NC	100
NPT 1/2"	8,0 - 15,0	0,3 - 1,3	16,0	21,3	25	25	24	27,5	40,5	KBET1NC	50
	13,5 - 21,0	0,4 - 1,3			30	30	29	33,0	41,5	KBET1LNC	
NPT 3/4"	8,0 - 15,0	0,3 - 1,3	16,0	26,7	25	25	27	27,5	40,5	KBET2SNC	50
	13,5 - 21,0	0,4 - 1,3			30	30	29	33,0	41,5	KBET2NC	
	18,0 - 27,0	0,4 - 1,6			40	40	40	44,5	48,2	KBET2LNC	
NPT 1"	18,0 - 27,0	0,4 - 1,6	21,0	33,4	40	40	40	44,5	48,2	KBET3SNC	30
	23,0 - 33,0	0,4 - 2,0			43	43	43	48,5	51,7	KBET3NC	
NPT 1 1/4"	29,0 - 40,0	0,4 - 2,0	21,0	42,2	52	52	52	59,0	55,2	KBET4NC	25
NPT 1 1/2"	35,0 - 48,0	0,4 - 2,5	21,0	48,3	60	60	60	66,5	67,5	KBET5SNC	20
	42,0 - 56,0	0,6 - 2,5			75	74	70	83,0	74,3	KBET5NC	
NPT 2"	42,0 - 56,0	0,6 - 2,5	21,0	60,3	75	74	70	83,0	74,3	KBET6SNC	10
	53,0 - 66,0				85	85	80	94,0	75,3	KBET6NC	
NPT 2 1/2"	53,0 - 66,0	0,6 - 2,5	21,0	73,0	85	85	80	94,0	75,3	KBET7SNC	5
	63,0 - 75,0				95	95	90	105,0	78,8	KBET7NC	